

COMPANY	PART NUMBER	DESCRIPTION	IN STOCK QTY.
Numatics	8501AK429465001	END PLATE KIT 501 SERIES 1/8" NPT	7
Numatics	R501A2B10MA00F1	Electrically-actuated solenoid pilot pneumatic directional control valve (Cv 0.42-0.47) with rubber-packed actuation; spring return + flush manual override - ASCO Numatics (501 Series (11mm)) - 2-position 4-way (5/2) - 24Vdc solenoid control voltage - ..	6
Numatics	R501A2B40MA00F1	Electrically-actuated double (dual) solenoid pilot pneumatic directional control valve (Cv 0.42-0.47) with rubber-packed actuation + flush manual override - ASCO Numatics (501 Series (11mm)) - 2-position 4-way (5/2) - 24Vdc solenoid control voltage - w...	22
Numatics	R501A2B50MA00F1	Electrically-actuated double (dual) solenoid pilot pneumatic directional control valve (Cv 0.42-0.47) with rubber-packed actuation + flush manual override - ASCO Numatics (501 Series (11mm)) - 3-position 4-way (5/3) open center dual pressure - 24Vdc so...	6
Numatics	K501AMM3FMA0010	Pneumatic manifold sub-base - 3 stations - side ports - double Z-board - ASCO Numatics (501 Series (11mm)) - with 3 stations - with 6mm push-in pneumatic ports - with Plug-in DC control connections (with indicating light) - IP65	2
Numatics	K501AK429465011	501 SERIES END PLATE	1
Numatics	P599AE502625001	MANIFOLD PART 501,502, 503 SERIES 26 PIN ROUND CONNECTOR & HOUSING	1

Numatics	<i>R501A2B70MA00F1</i>	Electrically-actuated double (dual) solenoid pilot pneumatic directional control valve (Cv 0.42-0.47) with rubber-packed actuation + flush manual override - ASCO Numatics (501 Series (11mm)) - 3-position 4-way (5/3) open to 2 & 4 in center - 24Vdc solenoid control voltage - with Plug-in DC control connections (with indicating light) - 11mm width - IP65	6
Numatics	<i>P580AEED1010A00</i>	Ethernet/IP DLR-compatible (Device Level Ring) communications module (node) with integrated web server + HTTP / FTP / UNICAST + fail-safe device settings + integrated 2-port sw. - ASCO Numatics (580 Series electronics) - with A-coded 4-pin M12 (male) p...	1
Numatics	<i>122BB400M000061</i>	Electrically-actuated pneumatic double (dual) solenoid pilot valve (Cv 0.56) with spool and sleeve actuation + flush manual override - without mounting - ASCO Numatics (2012 Series) - 2-position 4-way (5/2) - 24Vdc solenoid control voltage - with Plug-	1
Numatics	<i>P503AB428359001</i>	Blank station plate kit - ASCO Numatics	6
Numatics	<i>R503A2B50MA00F1</i>	Electrically-actuated double (dual) solenoid pilot pneumatic directional control valve (Cv 0.813-1.321) with rubber-packed actuation + flush manual override - ASCO Numatics (503 Series (26mm)) - 3-position 4-way (5/3) open center dual pressure - 24Vdc ...	6

Numatics	<i>R503A2B60MA00F1</i>	Electrically-actuated solenoid pilot pneumatic directional control valve (Cv 0.813-1.321) with rubber-packed actuation + flush manual override - ASCO Numatics (503 Series (26mm)) - 3-position 4-way (5/3) blocked / closed center - 24Vdc solenoid control...	6
Numatics	<i>353BB500M000061</i>	Electrically-actuated pneumatic double (dual) solenoid pilot valve (Cv 3.5) with spool and sleeve actuation + flush manual override - without mounting - ASCO Numatics (2035 Series) - 3-position 4-way (5/3) open center - 24Vdc solenoid control voltage -...	3
Numatics	<i>229-719</i>	End plate kit - ASCO Numatics - with 1/4" NPTF end plate ports + 1/8" NPTF manf. port	1
Numatics	<i>I34SS6002P00030</i>	Electrically-actuated pneumatic double direct solenoid valve (Cv 4.4) with spool and sleeve actuation + flush manual override - without mounting - ASCO Numatics (ISO 5599/2 Series) - 3-position 4-way (5/3) blocked / closed center - 110Vac-120Vac (50Hz/...	2
Numatics	<i>240-181</i>	Ethernet/IP communications module (node) with integrated web server + HTTP / FTP / UNICAST + fail-safe device settings - ASCO Numatics (G3 electronics Series) - with Single key 4-pin 7/8" MINI type (male) power connector + D-coded 4-pin M12 type (femal...	1

		Auto Recovery module (ARM) - Protects configuration information during a critical failure; allows configuration information to be saved and reloaded to replacement module automatically - ASCO Numatics (G3 electronics Series)	
Numatics	<i>240-182</i>		2
Numatics	<i>240-184</i>	Terminator module - ASCO Numatics (G3 electronics Series)	2
Numatics	<i>QA0405MK00000000</i>	M12 straight 4-pin male D-coded single-ended connector	3
Numatics	<i>240-205</i>	Digital I/O module with 16 x PNP digital inputs -	1
Numatics	<i>F22B-03</i>	PARTICULATE FILTER , FLEXIBLOK, 3/8IN NPTF, 5MICRON, 65SCFM, 150PSI)	15
Numatics	<i>P22B-03G</i>	3/8 FLTR/REG	7
Numatics	<i>M2MN</i>	1/4 METAL SILENCER	5
Numatics	<i>INB103-104-021</i>	Male connector 1/4 fitting	50
Numatics	<i>INB103-308-022</i>	3/8 X 3/8 MALE CONNECTOR	10
Numatics	<i>1FC1</i>	Inline Flow Control, 1/8" Inlet/Cylinder Port, NPT, Female,	9
Numatics	<i>3FCRN</i>	FLOW CONTROL VALVE, RIGHT ANGLE, 3/8INCH NPT , 175 PSI	9
Numatics	<i>2FPRN8</i>	1/4" x 1/4" NPT flow control	1
Numatics	<i>0750D01-12A-03</i>	M series cylinder	10
Numatics	<i>0875D04-01A-03</i>	M series cylinder	1